



Pronto EXTRA-Wetter Concentrated Surfactant 5 gallon pails

Appearance:	Green/Blue Liquid
Odor:	Slight
Boiling Point:	218F
Vapor Density:	Not Determined
pH:	Neutral
Flash Point:	N/A
Shipping Class:	55
Shipping Weight:	5 gal. pail 45lbs. 55 gal. drum 495lbs
Specific Gravity:	1.01
Solubility:	Emulsifiable
Reactivity:	Stable
HFIS Rating:	1-0-1
DOT Shipping Name:	Not hazardous



EXTRA-Wetter is effective in reducing asbestos fiber counts during removal and demolition operations. By using EXTRA-WETTER, the volume of water needed to wet and control the spread of dust and fiber particulate is reduced. This will aid in keeping work areas less messy. EXTRA-WETTER keeps particles wetter longer with less mess and with less application time by breaking up water droplets into finer mist, covering surfaces faster. Dilute 1:200. Diluted, surface tension is reduced from 100 dynes/sq.cm to 29 dynes/ sq. cm, ASTM #D 1331. NON-FLAMMABLE.

Directions:

1. Read and understand material safety data sheet when using this product.
2. Apply EXTRA-WETTER with any suitable low pressure spray applicator.
3. Mix one part EXTRA-WETTER with 200 parts water and spray onto all surfaces until thoroughly wetted. Use a course spray. Do not atomize.
4. Reapply when surfaces start to dry. Coverage and reapplication intervals will depend on surface characteristics, temperature and humidity.



TWIN CHEMICALS, INC.
6175 Hickory Flat Highway, Suite 110-344, Canton, GA, 30115
(800) 442-4958 / (770) 924-6147 Fax
www.twinchemicals.com

©2015 Twin Chemicals, Inc.



No Part of this publication may be reproduced or transmitted without the written consent of Twin Chemicals, Inc.