

Pro Clean No Odor Mastic Remover 5 gallon Pail and 55 Gallon Drum

Appearance:

Clear

Odor:

None

Boiling Point:

>300

Vapor Density:

Heavier than Air

pH:

Neutral

Flash Point:

>145 F (TCC)

Shipping Class:

55

Shipping Weight:

5 gal. pail 35 lbs.

55 gal. drum 386 lbs.

Specific Gravity:

Solubility:

Water emulsifiable

Coverage Rate:

Up to 150 sq. ft. per gallon

Reactivity:

Stable

HMIS Rating:

1-2-0

Shelf Life:

Indefinite

DOT Shipping Name: Not DOT Regulated On containers less than 120 gallons



Pro Clean is designed to give you the maximum power while still being in the no odor category. It quickly cuts through mastic to get the job done and has a superior surfactant system that allows for easy rinsing and final cleaning. This product will get the job done with fewer odor complaints while dissolving the mastic with the speed you need.

Directions:

- 1. Read and understand material safety data sheet when using this product.
- 2. Cover and dike walls, woodwork, drains and cracks.
- 3. Apply Pro Clean over all black mastic and adhesives. This may be done manually or with garden sprayer to 5' x 5' square areas.
- 4. Use a stiff bristled broom to agitate over the area. More than one application may be necessary.
- 5. Allow as little time as necessary to let Pro Clean penetrate and soften adhesive.
- 6. After the mastic is dissolved use a squeegee to clean up liquefied mastic and dispose of properly. The use of absorbents may aid in this process.
- 7. Aggressively clean surface with water and **Pronto Extra Wetter wetting agent** detergent for best results. Allow the surface to dry a minimum of 24-36 hours before applying new mastic and new flooring.





6175 Hickory Flat Highway, Suite 110-344, Canton, GA, 30115 (800) 442-4958 / (770) 924-6147 Fax www.twinchemicals.com ©2015 Twin Chemicals, Inc.



No Part of this publication may be reproduced or transmitted without the written consent of Twin Chemicals, Inc.