



Clean Air Low Odor Mastic Remover 5 gallon Pail and 55 Gallon Drum

Appearance:	Clear
Odor:	Extremely Low
Boiling Point:	>300
Vapor Density:	Heavier than Air
pH:	Neutral
Flash Point:	185F (TCC)
Shipping Class:	55
Shipping Weight:	5 gal. pail 35 lbs. 55 gal. drum 386 lbs.
Specific Gravity:	.818
Solubility:	Water emulsifiable
Coverage Rate:	Up to 150 sq ft per gallon
Reactivity:	Stable
HMIS Rating:	1-2-0
Shelf Life:	None
DOT Shipping Name:	Not DOT Regulated On containers less than 120 gallons



Clean Air Low Odor Mastic Remover is an economical, fast acting, low odor mastic remover. This product is a hydro-treated petroleum base with a superior surfactant system that allows for easy rinsing and final cleaning. This product is a contractor favorite because it gets the job done and is extremely cost effective.

Directions:

1. Read and understand material safety data sheet when using this product.
2. Cover and dike walls, woodwork, drains and cracks.
3. Apply Clean Air Mastic Remover over all black mastic and adhesives. This may be done manually or with garden sprayer to 5' x 5' square areas.
4. Use a stiff bristled broom to agitate over the area. More than one application may be necessary.
5. Allow as little time as necessary to let Clean Air Mastic Remover penetrate and soften adhesive.
6. After the mastic is dissolved, use a squeegee to clean up liquefied mastic and dispose of properly. The use of absorbents may aid in this process.



TWIN CHEMICALS, INC.
6175 Hickory Flat Highway, Suite 110-344, Canton, GA, 30115
(800) 442-4958 / (770) 924-6147 Fax
www.twinchemicals.com
©2015 Twin Chemicals, Inc.



No Part of this publication may be reproduced or transmitted without the written consent of Twin Chemicals, Inc.