



1606 UNIVERSAL LATEX PRIMER

DESCRIPTION

A pure acrylic latex primer for wood, metal or concrete. For use interior or exterior.

USES

Apply on steel, slate, aluminum, wood, galvanized and other non-porous surfaces. Use as a rust inhibitive primer. Use over spalled reinforced concrete where re-bar is showing. Prevents sap staining of unprimed wood, and water stains in ceiling panels. Markedly reduces corrosion of ferrous metal and enhances adhesion of topcoats over chalky surfaces.

SURFACE PREPARATION

Surface to be painted must be clean and dry. Remove all dirt, excess chalky residue, oils, grease, mildew or other surface contaminants. Make sure surface is completely dry before application.

APPLICATION

Use brush, roller or spray to apply.

LIMITATION OF LIABILITY

This product is manufactured to rigid control specifications. It is impossible to control the use and application. Therefore, the manufacturers sole liability is limited to replacing quantities of product proven to be defective. The manufacturer disclaims any liability for the cost of labor to repaint or any other use of the product.

Page 1 of 2

TECHNICAL DATA

PRODUCT NUMBER: 1606

RESIN: Acrylic Latex

COLOR: White/Grey

GLOSS: Flat

SOLID CONTENT:

BY WEIGHT: 56.2%

BY VOLUME: 40.9%

RECOMMENDED COVERAGE:

300 to 600 Sq.Ft./gal. per coat depending upon substrate. Apply liberally on rusty or slightly chalky surfaces. Recommend 2 coats for woods with heavy sap content.

% PIGMENT BY WEIGHT: 35.1

% VEHICLE BY WEIGHT: 64.9

VISCOSITY: 88 KU

WEIGHT PER GALLON: 11.3 lbs.

FLASH POINT: None

DRYING TIME: 70 F 50% R.H

Touch - 1/4 to 1/2 hour

Recoat - 2 to 3 hours

Full Cure - 12 hours

Do not apply at temperatures below 50 F or when rain, darkness or cold are imminent.

THINNER/CLEANUP: Water

TINTING: Not applicable

VOC: 98.0 grams/liter

AVAILABLE IN QTS, 1 & 5 GALLON PAILS

Revised 5-17 Supersedes all prior publications

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID;** if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

