



SUPER LIFE® ATV/UTV 4T **PREMIUM 4-STROKE ATV/UTV MOTOR OILS**

SUPER LIFE® ATV/UTV 4T Products are specially designed to meet the demands of recreational and utility of ATVs (All-Terrain Vehicles) and UTVs (Utility Vehicles). They provide the proper frictional properties for wet clutch system and gearbox durability. They are formulated with high quality base stocks and a unique additive package chosen for exceptional wear protection, sludge and varnish resistance, film strength, shear and thermal stability.

APPLICATIONS:

SUPER LIFE® ATV/UTV 4T Products are recommended for all types of 4-stroke ATVs /UTVs of manufacturers including POLARIS, HONDA, SUZUKI, YAMAHA, KAWASAKI, CAN-AM, KUBOTA, JOHN DEERE, ARCTIC CAT, BOMBARDIER, etc.

API SN
JASO MA/MA 2

BENEFITS:

- Help engine reach maximum horsepower.
- Anti-wear properties, lower corrosion and friction. Provide excellent protection for transmissions and wet clutches.
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly .
- Prolong engine life .
- Provide good characteristics in harmful deposit control to help keep the engine and gearbox running cleaner and provides good gearbox protection for incorporated gearboxes .

TYPICAL CHARACTERISTICS

Test	Method	Typical Results		
SAE Viscosity grade	SAE J300	10W-30	10W-40	20W-50
API Gravity	ASTM D287	31.64	30.77	29.85
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.87	0.872	0.877
Viscosity @ 40°C cSt @ 100°C cSt	ASTM D445	70.6 10.70	98.10 14.30	161.47 18.89
Viscosity Index	ASTM D2270	140	150	132
Flash Point, °C (°F)	ASTM D92	210(410)	225(437)	232(450)
Pour Point, °C (°F)	ASTM D97	-30(-22)	-30(-22)	-28(-18)
Noack, wt%	ASTM D5800	12.5	11.5	8.42
Total Base Number, mgKOH/g	ASTM D2896	7.0	7.0	7.0

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference MSDS Number 12021 database on our website at www.amtecol.com

