

**SAF 30 (5-15-45)**

-

**SECTION 1 Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Trade name : SAF 30 (5-15-45)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use : Industrial.

**1.3. Details of the supplier of the safety data sheet**

Company identification : AEC POLYMERS  
 Z.I. Eyrialis  
 33114 LE BARP FRANCE  
 Tél: +33 (0) 5.57.26.15.15

Distributed by: Composite Essential Materials, LLC  
 315 NW Peacock Blvd.  
 Port St. Lucie, FL 34986  
 essential.composites@gmail.com

Name and function of the responsible person : Mr Roux - aecpolymers@wanadoo.fr

**1.4. Emergency telephone number**

Phone nr : ORFILA  
 +33 (0)1.45.42.59.59

24 Hour Response Number:

800-535-5053 Infotrac Account No. 106236

**SECTION 2 Hazards identification**

**Label elements**

Risk Phrases : The product may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect.

Hazards identification **Highly flammable liquid and vapour**  
**Causes serious eye irritation**  
**Causes skin irritation**  
**May cause an allergic skin reaction**  
**May cause respiratory irritation**

Primary route of exposure : Skin and eyes contact.

**Symptoms relating to use**

- Ingestion : Must not come into contact with food or be consumed.

**2.1. Classification of the substance or mixture**

**Classification EC 67/548 or EC 1999/45**

Classification : F; R11  
 Xi; R36/37/38  
 R43

**Hazard Class and Category Code(s), Regulation (EC) No 1272/2008 (CLP)**

- Health hazards : Skin irritation - Category 2 - Warning - (CLP : Skin Irrit. 2) - H315  
 Eye irritation - Category 2A - Warning - (CLP : Eye Irrit. 2) - H319  
 Skin sensitisation - Category 1 - Warning - (CLP : Skin Sens. 1) - H317  
 Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation - Category 3 - Warning (CLP : STOT SE 3)
- Physical hazards : Flammable liquids - Category 2 - Danger - (CLP : Flam. Liq. 2) - H225
- Environmental hazards

**2.2. Label elements**

**Labelling EC 67/548 or EC 1999/45**

Symbol(s)



**SAF 30 (5-15-45)**

-

**SECTION 2 Hazards identification (continued)**

**R Phrase(s)** : Xi : Irritant  
 F : Highly flammable  
 : R11 : Highly flammable.  
 R36/37/38 : Irritating to eyes, respiratory system and skin.  
 R43 : May cause sensitization by skin contact.

**S Phrase(s)** : S37 : Wear suitable gloves.

**Labelling Regulation EC 1272/2008 (CLP)**

• Hazard pictograms



• Hazard pictograms : SGH02 - SGH07

• Signal words : Danger

• Hazard statements : H225 - Highly flammable liquid and vapour  
 H319 - Causes serious eye irritation  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H335 - May cause respiratory irritation

• Precautionary statements

**Prevention** : NA - Keep away from ignition sources such as heat, sparks and open flame. – No smoking.  
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P233 - Keep container tightly closed  
 P273 - Avoid release to the environment

**Response** : P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P310 - Immediately call a POISON CENTER or doctor/physician  
 P333+313 - If skin irritation or rash occurs: Get medical advice/attention

**Storage** : P403+233 - Store in a well-ventilated place. Keep container tightly closed

**2.3. Other hazards**

**Other hazards** : None under normal conditions.

**SECTION 3 Composition/information on ingredients**

**3.1./3.2. Substance / Preparation**

**Components** : This product is hazardous.

| Substance name   | Contents              | CAS No     | EC No     | Annex No     | Ref REACH | Classification  |
|--|-----------------------|------------|-----------|--------------|-----------|---|
| Methyl methacrylate                                      | : Between 35 and 50 % | 80-62-6    | 201-297-1 | 607-035-00-6 | ----      | F; R11<br>Xi; R37/38<br>R43<br>-----<br>Flam. Liq. 2;H225<br>Skin Irrit. 2;H315<br>STOT SE3;H335<br>Skin Sens. 1;H317 |
| 2-Propenoic acid, 2-methyl-,2-hydroethyl ester,phosphate | : Between 1 and 5 %   | 24599-21-1 | 246-342-6 | -----        | ----      | C; R34<br>Xi; R37<br>R43<br>-----<br>Skin Corr. 1B;H314<br>STOT SE3;H335<br>Skin Sens. 1;H317                         |
| Methacrylic acid   | : Between 1 and 5 %   | 79-41-4    | 201-204-4 | 607-088-00-5 | ----      | Xn; R21/22<br>C; R35<br>-----<br>Not CLP<br>Acute Tox. 4 (Dermal);H312<br>Acute Tox. 4 (Oral);H302                    |

## SAF 30 (5-15-45)

-

### SECTION 3 Composition/information on ingredients (continued)

| Substance name   | Contents             | CAS No      | EC No     | Annex No     | Ref REACH             | Classification   |
|--|----------------------|-------------|-----------|--------------|-----------------------|--|
| Reaction product: bisphenol-A- ( epichlorhydrin) epoxy resin ( number average molecular weight <= 700) | Between 1 and 5 %    | 25068-38-6  | 500-033-5 | 603-074-00-8 | ----                  | Xi; R36/38<br>R43<br>N; R51-53<br>-----<br>Eye Irrit. 2;H319<br>Skin Irrit. 2;H315<br>Skin Sens. 1;H317<br>Aquatic Chronic 2;H411  |
| Diméthacrylate de zinc   | Between 0.01 and 1 % | 13189-00-9  | 236-144-8 | -----        | ----                  | Xn; R22<br>Xi; R41<br>R43<br>N; R50<br>-----<br>Eye Dam. 1;H318<br>Acute Tox. 4 (Oral);H302<br>Skin Sens. 1;H317<br>Aquatic Acute 1;H400                                       |
| 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene   | Between 0.01 and 1 % | -----       | 423-300-7 | 616-198-00-2 | 01-0000016979-49-0001 | R43<br>R53<br>-----<br>Skin Sens. 1;H317<br>Aquatic Chronic 4;H413   |
| N,N-dimethyl-p-toluidine   | Between 0.01 and 1 % | 99-97-8     | 202-805-4 | 612-056-00-9 | ----                  | T; R23/24/25<br>R33<br>R52-53<br>-----<br>Acute Tox. 3 (Dermal);H311<br>Acute Tox. 3 (Inhalation);H331<br>Acute Tox. 3 (Oral);H301<br>STOT RE 2;H373<br>Aquatic Chronic 3;H412 |
| Silicone acrylate  | Between 0.01 and 1 % | 125455-52-9 | 603-070-6 | -----        | ----                  | R43<br>-----<br>Skin Sens. 1;H317  |
| 1,1'-(p-tolylimino)dipropan-2-ol   | Between 0.01 and 1 % | 38668-48-3  | 254-075-1 | -----        | 01-2119980937-17      | T; R25<br>Xi; R36<br>R52-53<br>-----<br>Acute Tox. 2 (Oral);H300<br>Eye Irrit. 2;H319<br>Aquatic Chronic 3;H412  |
| 1-methoxy-2-propanol, monopropylene glycol methyl ether  | Between 0.1 and 1 %  | 107-98-2    | 203-539-1 | 603-064-00-3 | 01-2119457435-35      | R10<br>R67<br>-----<br>Flam. Liq. 3;H226<br>Not CLP  |

### SECTION 4 First aid measures

#### 4.1. Description of first aid measures

- **General information** : Take off immediately all contaminated clothing.
- First aid measures**
- Inhalation** : Remove victim to fresh air. Assure fresh air breathing.  
If breathing is difficult, give oxygen.  
Obtain medical attention.
- Skin contact** : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- Eye contact** : Rinse immediately with plenty of water.  
Ensure adequate flushing of eyes by separating eyelids with the fingers. Obtain medical attention if pain, blinking, tears or redness persist.
- Ingestion** : Rinse mouth. Do not induce vomiting. Seek medical attention if ill effect develops.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact.  
Skin and eyes irritant.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

**SAF 30 (5-15-45)**

-

**SECTION 5 Firefighting measures**

**5.1. Extinguishing media**

**Extinguishing media** : Dry powder. Water fog. Carbon dioxide (CO2). Foam.

**5.2. Special hazards arising from the substance or mixture**

**Specific hazards** : May form flammable vapour-air mixture.

**Hazardous combustion products** : Toxic gases. (COx)

**5.3. Advice for firefighters**

**Protection against fire** : Do not enter fire area without proper protective equipment, including respiratory protection.

**Prevention** : Keep away from sources of ignition. No smoking.

**Special procedures** : Exercise caution when fighting any chemical fire.

**Surrounding fires** : Use water spray or fog for cooling exposed containers.

**SECTION 6 Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For emergency responders** : In case of insufficient ventilation, wear suitable respiratory equipment. Keep public away from danger area. Equip cleanup crew with proper protection. No smoking.  
 Do not get in eyes, on skin, or on clothing

**6.2. Environmental precautions**

**Environmental precautions** : Spread coarse, inert granular cover such as sand, on any affected walking surface. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

**6.3. Methods and material for containment and cleaning up**

**Clean up methods** : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Clean up any spills as soon as possible, using an absorbent material to collect it. Use suitable disposal containers.  
 Incinerate.

**6.4. Reference to other sections**

See Heading 8.

**SECTION 7 Handling and storage**

**7.1. Precautions for safe handling**

**Handling** : Do not breathe vapour. Wear proper protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Technical protective measures** : Use grounded electrical/mechanical equipment.

**General** : Vapours may be heavier than air.  
 Keep away from sources of ignition. No smoking.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage** : Keep container tightly closed and at a temperature not exceeding . 25°C  
 Keep only in the original container in a cool, well ventilated place. Keep in fireproof place. Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.  
 Keep away from combustible material.

**Precautions in handling and storage** : Good ventilation of the workplace required.

**7.3. Specific end use(s)**

**SAF 30 (5-15-45)**

-

**SECTION 7 Handling and storage (continued)**

Not applicable.

**SECTION 8 Exposure controls/personal protection****8.1. Control parameters**

Methyl methacrylate : VME - France [ppm] : 100  
Methyl methacrylate : VME - France [mg/m<sup>3</sup>] : 410  
Methyl methacrylate : VLE - France [ppm] : 200  
Methyl methacrylate : VLE - France [mg/m<sup>3</sup>] : 820  
Methyl methacrylate : TLV<sup>©</sup> -STEL [ppm] : 100  
Methyl methacrylate : TLV<sup>©</sup> -TWA [ppm] : 50  
N,N-dimethyl-p-toluidine : TLV<sup>©</sup> -TWA [ppm] : 2 (Toluidine)  
1-methoxy-2-propanol, monopropylene glycol methyl ether : VME - France [ppm] : 100  
1-methoxy-2-propanol, monopropylene glycol methyl ether : VME - France [mg/m<sup>3</sup>] : 360  
1-methoxy-2-propanol, monopropylene glycol methyl ether : TLV<sup>©</sup> -STEL [ppm] : 150  
1-methoxy-2-propanol, monopropylene glycol methyl ether : TLV<sup>©</sup> -TWA [ppm] : 100  
1-methoxy-2-propanol, monopropylene glycol methyl ether : ILV (EU) - 15 min - [ppm] : 150  
1-methoxy-2-propanol, monopropylene glycol methyl ether : ILV (EU) - 15 min - [mg/m<sup>3</sup>] : 568  
1-methoxy-2-propanol, monopropylene glycol methyl ether : ILV (EU) - 8 H - [ppm] : 100  
1-methoxy-2-propanol, monopropylene glycol methyl ether : ILV (EU) - 8 H - [mg/m<sup>3</sup>] : 375

**8.2. Exposure controls**

- **Respiratory protection** : In case of insufficient ventilation, wear suitable respiratory equipment. ABEK (EN14387)
- **Hand protection** : For prolonged contact, use nitrile or neoprene gloves or other material resistant to petroleum oils. (EN374)
- **Skin protection** : Wear impervious rubber safety shoes.  
Wear suitable protective clothing.
- **Eye protection** : Chemical goggles or safety glasses. EN166
- **Ingestion** : When using, do not eat, drink or smoke.
- Industrial hygiene** : Provide good ventilation in process area to prevent formation of vapour.

**SECTION 9 Physical and chemical properties****9.1. Information on basic physical and chemical properties****9.1.a. Appearance**

**Physical state at 20 °C** : Viscous liquid.  
**Colour** : Creme.

**9.1.b. Odour**

**Odour** : Characteristic.

**9.1.d. pH****9.1.f. Initial boiling point - boiling range**

**Boiling point [°C]** : 100°C [CAS 80-62-6]  
**Final boiling point [°C]** : No data available.

**9.1.g. Flash point**

**Flash point [°C]** : 20

**9.1.i. Flammability****9.1.k. Vapour pressure**

**SAF 30 (5-15-45)**

-

**SECTION 9 Physical and chemical properties (continued)**

Vapour pressure : No data available.

Vapour pressure, 50°C : No data available.

**9.1.m. Relative density**

Density : 1,0-1,05

**9.1.n. Solubility**

Solubility in water : No data available.

**9.1.o. Partition coefficient : n-octanol / water**

Log P octanol / water at 20°C : No data available.

**9.1.p. Auto-ignition temperature**

Auto-ignition temperature [°C] : No data available.

**9.1.q. Thermal decomposition**

**9.1.r. Viscosity**

Viscosity at 20°C [mPa.s] : 130000 - 140 000

**9.1.s. Explosive Properties**

Explosion limits - lower [%] : No data available.

Explosion limits - upper [%] : No data available.

**9.1.t. Oxidising properties**

**9.2. Other information**

Acid/alkali reserve [g NaOH/100g] : No data available.

Critical temperature [°C] : No data available.

**SECTION 10 Stability and reactivity**

**10.1. Reactivity**

**10.2. Chemical stability**

Stability : Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Hazardous reactions : No data available.

**10.4. Conditions to avoid**

Conditions to avoid : Keep away from ignition sources such as heat, sparks and open flame. – No smoking.  
 Keep container tightly closed and at a temperature not exceeding . 20°C Sparks.  
 Overheating.  
 Protect from sunlight

**10.5. Incompatible materials**

Materials to avoid : Peroxides.  
 Strong oxidizers.  
 Strong acids.  
 Strong bases.

**10.6. Hazardous decomposition products**

Hazardous decomposition products : According to process conditions, hazardous decomposition products may be generated.

**SAF 30 (5-15-45)**

-

**SECTION 11 Toxicological information**

**11.1. Information on toxicological effects**

**Toxicity information**

- **Acute toxicity** : Rat oral LD50 [mg/kg] 7900-9400 [CAS 80-62-6]
- **Skin corrosion/irritation** : No data available.
- **Serious eye damage/irritation** : Eye irritation - Category 2A - Warning - (CLP : Eye Irrit. 2) - H319
- Rat inhalation LC50 [mg/l/4h]** : No data available.
- **Respiratory or skin sensitisation** : Skin irritation - Category 2 - Warning - (CLP : Skin Irrit. 2) - H315
- **Germ cell mutagenicity** : No data available.
- Rat inhalation [mg/l] (6 hours / 24 hours)** : No data available.
- **Carcinogenicity** : No data available.
- **Reproductive toxicity** : No data available.
- **STOT-single exposure** : May cause respiratory irritation
- **STOT-repeated exposure** : No data available.
- Rabbit dermal LD50 [mg/kg]** : No data available.
- **Aspiration hazard** : No data available.
- Rabbit-rat dermal [mg/kg/24 hours]** : No data available.
- Rat oral LD50 [mg/kg]** : No data available.
- Rat oral LD50 [mg/kg/24h]** : No data available.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Undesirable human health effects** : Exposure may produce cough, mucous, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.  
 Slight irritant by ingestion.  
 Repeated or prolonged skin contact may cause irritation.  
 Irritating to eyes.

**SECTION 12 Ecological information**

**12.1. Toxicity**

- Ecological effects information** : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**LC50-96 Hour - fish [mg/l]** : 79 [CAS 80-62-6 ]

**48 Hour-EC50 - Daphnia magna [mg/l]** : 69 [CAS 80-62-6 ]

**IC50 72h Algae [mg/l]** : 110 [CAS 80-62-6 ]

**12.2. Persistence and degradability**

- Persistence - degradability** : Potentially biodegradable. 94% [cas :80-62-6]

**12.3. Bioaccumulative potential**

- Bioaccumulative potential** : 1.38 logK(o/w) [cas :80-62-6]

**12.4. Mobility in soil**

**12.5. Results of PBT and vPvB assessment**

**12.6. Other adverse effects**

**SAF 30 (5-15-45)**

-

**SECTION 13 Disposal considerations**

**13.1. Waste treatment methods**

Dispose in a safe manner in accordance with local/national regulations.

- General** : Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations.
- Disposal method** : Dispose of contents and/or container in accordance with local, regional, national and/or international regulation. Incineration is recommended
- Industrial waste number** : 08 04 09 - Waste adhesives and sealants containing organic solvents or other dangerous substances. (Hazardous waste pursuant to Directive 91/689/EEC on hazardous waste)

**SECTION 14 Transport information**

**14.1. UN number**

1133

Labelling



**14.2. UN proper shipping name**

: ADHESIVES (Methyl methacrylate)

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

II

**14.5. Environmental hazards**

No data available.

**14.6. Special precautions for user**

No special work practices are needed beyond the above recommendations under anticipated conditions of normal use.

**SECTION 15 Regulatory information**

**Pictograms (Precautionary statements)**

- Health hazards** : Skin irritation - Category 2 - Warning - (CLP : Skin Irrit. 2) - H315  
 Eye irritation - Category 2A - Warning - (CLP : Eye Irrit. 2) - H319  
 Skin sensitisation - Category 1 - Warning - (CLP : Skin Sens. 1) - H317  
 Specific Target Organ Toxicity - Single exposure - Respiratory tract irritation - Category 3 - Warning (CLP : STOT SE 3)

**EC Labelling**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Physical hazards** : Flammable liquids - Category 2 - Danger - (CLP : Flam. Liq. 2) - H225
- Environmental hazards** : Hazardous to the aquatic environment - Chronic hazard - Category 3 - (CLP : Aquatic Chronic 3) - H412

Ensure all national/local regulations are observed.

**SAF 30 (5-15-45)**

-

**SECTION 15 Regulatory information (continued)**

**15.2. Chemical safety assessment**

• Hazard pictograms



**Signal words** : Danger

No data available.

**EC Classification** : F; R11  
 67/548/EC & 1999/45/EC Xi; R36/37/38  
 R43

**Hazard statements** : Highly flammable liquid and vapour  
 Causes serious eye irritation  
 Causes skin irritation  
 May cause an allergic skin reaction  
 May cause respiratory irritation

*Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006.*

*Directive 2006/121/EC of the European Parliament and of the Council of 18 December 2006.*

• Precautionary statements

**Symbol(s)** : Xi : Irritant  
 F : Highly flammable

**R Phrase(s)** : R11 : Highly flammable.  
 R36/37/38 : Irritating to eyes, respiratory system and skin.  
 R43 : May cause sensitization by skin contact.

• **Prevention** : Keep away from ignition sources such as heat, sparks and open flame. – No smoking.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Keep container tightly closed  
 Avoid release to the environment

**S Phrase(s)** : S37 : Wear suitable gloves.


• **Response** : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
 Rinse skin with water/shower  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor/physician  
 If skin irritation or rash occurs: Get medical advice/attention

• **Storage** : Store in a well-ventilated place. Keep container tightly closed

**CLP classification**

*REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006*

• Pictograms (Precautionary statements)



**Hazard Class and Category Code**  
**REGULATION (EC) No 1272/2008 (CLP)**

**SAF 30 (5-15-45)**

-

**SECTION 15 Regulatory information (continued)**

**Special labelling** : Contains : Methyl methacrylate - 2-Propenoic acid, 2-methyl-,2-hydroethyl ester, phosphate - Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700) - Diméthacrylate de zinc - 1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene - Silicone acrylate. May produce an allergic reaction.

**SECTION 16 Other information**

**List of relevant R phrases (§ 3)** : H225 - Highly flammable liquid and vapour  
 H226 - Flammable liquid and vapour  
 H300 - Fatal if swallowed  
 H301 - Toxic if swallowed  
 H302 - Harmful if swallowed  
 H311 - Toxic in contact with skin  
 H312 - Harmful in contact with skin  
 H314 - Causes severe skin burns and eye damage  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H318 - Causes serious eye damage  
 H319 - Causes serious eye irritation  
 H331 - Toxic if inhaled  
 H335 - May cause respiratory irritation  
 H336 - May cause drowsiness or dizziness  
 H373 - May cause damage to organs ... through prolonged or repeated exposure  
 ....  
 H400 - Very toxic to aquatic life  
 H411 - Toxic to aquatic life with long lasting effects  
 H412 - Harmful to aquatic life with long lasting effects  
 H413 - May cause long lasting harmful effects to aquatic life

R10 : Flammable.  
 R11 : Highly flammable.  
 R21/22 : Harmful in contact with skin and if swallowed.  
 R22 : Harmful if swallowed.  
 R23/24/25 : Toxic by inhalation, in contact with skin and if swallowed.  
 R25 : Toxic if swallowed.  
 R33 : Danger of cumulative effects.  
 R34 : Causes burns.  
 R35 : Causes severe burns.  
 R36 : Irritating to eyes.  
 R36/38 : Irritating to eyes and skin.  
 R37 : Irritating to respiratory system.  
 R37/38 : Irritating to respiratory system and skin.  
 R41 : Risk of serious damage to eyes.  
 R43 : May cause sensitization by skin contact.  
 R50 : Very toxic to aquatic organisms.  
 R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R53 : May cause long-term adverse effects in the aquatic environment.  
 R67 : Vapours may cause drowsiness and dizziness.

**Revision** : 3  
**Print date** : 22 / 9 / 2015

The contents and format of this SDS are in accordance with REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

**SAF 30 (5-15-45)**

End of document