



## DURALIFE® GEAR 1 - GEAR OILS

**Duralife® Gear 1 – Gear Oils** are formulated with selected base oils and additives for protection of manual transmissions, transaxles and most types of gearboxes, bearing in passenger cars, trucks, buses and vans.

### APPLICATIONS:

**Duralife® Gear 1 – Gear Oils** meet the requirement of the car and truck manufacturers who specify the use of an oil meeting API GL-1.

- ❖ API GL-1

### BENEFITS:

- Maintain strong oil film under high loading conditions.
- Good thermal stability.
- Good anti-wear, antirust, anticorrosion, antifoam properties.

### TYPICAL CHARACTERISTICS

Test	Method	Typical results	
SAE Grade		90	140
API Gravity	ASTM D 287	25.72	22.30
Specific Gravity @ 15.6°C (60°F)	ASTMD 1298	0.90	0.92
Viscosity @ 40°C, cSt	ASTMD 445	163	400
@ 100°C, cSt		15.4	28.5
Viscosity Index	ASTM D 2270	95	95
Flash Point, °C (°F)	ASTM D92	200(392)	200(392)
Pour Point ,°C(°F)	ASTM D97	-9 (15.8)	-9 (15.8)

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

### WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers.

Reference SDS Number 12026 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link

