



THE BEST CHOICE BELOW GRADE – NOW BETTER THAN EVER

STYROFOAM™ BRAND EXTRUDED POLYSTYRENE INSULATION CAN BE LEFT EXPOSED IN BASEMENTS

Now, the product you've trusted *outside* the home for more than 60 years offers more insulation options *inside*. All STYROFOAM™ Brand XPS Insulation up to 2" thick can be installed and left exposed in basements per Code Report ICC-ESR 2142.

Looking to offer homeowners a warm, comfortable basement that is remodel-ready?

STYROFOAM™ Brand XPS Insulation can be installed directly to masonry walls, offering a solid layer of moisture-resistant insulating comfort in one easy step. The widely recognized BLUE™ rigid insulation boards can be left exposed (up to 2"), creating a semi-finished basement that is remodel-ready.

Outperform the ordinary with STYROFOAM™ Brand XPS Insulation and offer your customers a warm, comfortable basement that is quicker and easier to insulate than traditional methods.

Why Choose STYROFOAM™ Brand XPS Insulation?

- Quick and easy to install – saving time and money on the job
- Can be left exposed – remodel-ready
- Excellent moisture resistance
- Thermally efficient – delivering high R-value of 5.0 per inch
- Lightweight, easy to cut and compatible with standard construction adhesives
- Versatile – available in a selection of edge treatments, sizes and thicknesses
- 50-year thermal limited performance warranty*

FINISH THE JOB WITH....

GREAT STUFF PRO™ Wall & Floor Adhesive**	FROTH-PAK™ Foam Insulation**
	
<p>Adhere insulation boards to the basement wall with GREAT STUFF PRO™ Wall & Floor Adhesive.</p> <ul style="list-style-type: none"> • Single-component, moisture-cured foam • Fast-grab tack and long-term bond • Excellent adhesion to foam panels and masonry, as well as lumber, plywood, particleboard, concrete and drywall 	<p>Insulate the full height of the basement wall and achieve a complete and continuous thermal finish from floor to band joist.</p> <ul style="list-style-type: none"> • Two-component, quick-cure foam • Fills cavities, cracks and expansion joints for insulation and air sealing • One of the easiest and most effective ways to weatherize existing and new homes • UL classified R7813 • ASTM E84 Class A rating (flame spread of 25 or less)

* In the United States, a 50-year thermal limited warranty is available on STYROFOAM™ Brand Insulation products 1.5" thick and greater. For thickness less than 1.5", other warranties may apply. Warranties are available as described at www.dbswarranties.com.

**Read the label/instructions and Material Safety Data Sheets carefully before use.

For Technical Information: 1-866-583-BLUE (2583) • For Sales Information: 1-800-232-2436
THE DOW CHEMICAL COMPANY • Dow Building Solutions • 200 Larkin, Midland, MI 48674
www.insulateyourhome.com



NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

STYROFOAM™ Brand Extruded Polystyrene Foam Insulation

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

Dow Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

For proper ventilation of combustion appliances, see <http://www.epa.gov/iaq/homes/hip-ventilation.html>.

FROTH-PAK™ Spray Polyurethane Foam contains isocyanate, hydrofluorocarbon blowing agent and polyol. Read the instructions and Material Safety Data Sheets carefully before use. Wear protective clothing (including long sleeves), gloves, goggles or safety glasses, and proper respiratory protection. Do not breathe vapor or mist. Use only with adequate ventilation. It is recommended that applicators and those working in the spray area wear respiratory protection. Increased ventilation significantly reduces the potential for isocyanate exposure, however, supplied air or an approved air-purifying respirator equipped with an organic vapor sorbent and a particulate filter may still be required to maintain exposure levels below ACGIH, OSHA, WEEL or other applicable limits. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure, air-supplying respirator (air line or self-contained breathing apparatus). Spraying large amounts of foam indoors may require the use of a positive pressure, air-supplying respirator. Contents under pressure.

GREAT STUFF PRO™ sealant and adhesive products contain isocyanate and a flammable blowing agent. Read the label and Material Safety Data Sheet carefully before use. Eliminate all sources of ignition before use. Wear long sleeves, gloves, and safety glasses or goggles. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure.

When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers, are properly vented to the outside. See <http://www.epa.gov/iaq/homes/hip-ventilation.html>.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

