



# TruStop I Surface Mount



## TruStop I Features:

- Grout Elongation: 44%
- USDA Approved
- Environmentally Friendly
- Easy to Use
- Worker Friendly
- Can be used on virtually any surface
- Use on Cracks, Manholes, Vaults, even Dams

TruStop I Surface Mount Crack Injection Kits contain all you need for any crack repair, the materials are easy to use and worker and environmentally friendly. Our three part system contains, Grout, Catalyst and Injection Ports; to be used with HouseGuard Grease Guns (sold separately). TruStop I Surface Mount Grout is a multipurpose injection resin designed to seal leaking cracks, voids or fractures in concrete surfaces. TruStop I Surface Mount Catalyst is used in conjunction with our Grout. For example, when using TruStop I Surface Mount Grout a 15-second reaction time may be achieved by mixing one pint of TruStop I Surface Mount Catalyst to five-gallons of Grout. Faster reaction times may be achieved by use of additional Catalyst. TruStop I Surface Mount Injection Ports are 5/8" mechanical ports constructed of a brass stem, extruded rubber bladder and 1/4" X 28 grease fitting. TruStop I Surface Mount Crack Injection Kits come in three sizes: the Sample Kit, equipped with enough product to repair up to 2 cracks ; the Starter Kit, will supply you with the right amount of product to complete up to 14 cracks and the Bulk Kit, a larger quantity of product for up to as many as 60 cracks.

## Grout

### TEST TYPE

Density

Water Absorption  
(Volume Confined)

Shear Strength

Tensile Strength

Elongation

Viscosity

Color

UL Listed(NSF-61-1989)

### RESULTS

2 lbs.

<1%

17.10 PSI

29.30 PSI

44%

@500CPS

Amber

**USDA Approved YES**

### TEST METHOD

ASTM D-1622

ASTM D-2127

ASTM C-273

ASTM D-1623

ASTM D-1623



Injection Port

**USDOT Shipping Data UNREGULATED, CLASS 55**



8600 Berk Blvd. Hamilton, Oh 45015 ••• 800.560.5701

TST03-09

