

The Datacard® CR500™

instant issuance system turns

blank white stock into highly

customized, ready-to-use

credit, debit and ATM cards

instantly. Issuing financial

cards instantly minimizes

wait times, reduces costs

and lowers the risk of lost

or stolen cards. You can

give cardholders instant

purchasing power and begin

generating card-based

revenue immediately.

Instantly issue personalized, unembossed financial cards

The Datacard® CR500™ instant issuance system — integrated with Datacard® CardWizard® issuance software — empowers banks, credit unions, retailers and service bureaus to print ready-to-use, flat financial cards on demand. With instant issuance, customers get customized financial cards and immediate purchasing power — which means more revenue, higher activation rates, increased card usage and enhanced customer loyalty. This secure system prints brilliant, full-color photos, logos, text and graphics. A full range of smart card and magnetic stripe options makes it ideal for a wide range of programs. Because the system is smart card-ready, it helps make the transition to EMV® chip-based cards seamless and secure.

Outstanding consistency, reliability and security

- Produce high-quality, custom cards with two-sided printing, magnetic stripe encoding and contact and contactless smart card encoding to ISO standards
- Reduce costs associated with paper, mailing and outsourcing
- Provide personalized customer service and create cross-selling opportunities with instant on-site issuance
- Minimize card inventory and preprinting costs by using blank stock to generate standard and custom cards
- Increase efficiency with multi-card hopper for generating credit, debit or ATM cards
- Enhance security by protecting card stock, supplies and rejected cards with dual-control access to the card issuing system
- Comply with VISA and MasterCard security requirements
- Protect sensitive data from unauthorized interception during network transmission with SSL/TSL encryption



DATACARD® CR500™ INSTANT ISSUANCE SYSTEM

Standard Features

Printing method

Dye-sublimation retransfer printing

Print resolution

300 dots per inch (dpi)

Print speed

Delivers a four-color, one-sided card in 36 seconds or one two-sided card in 65 seconds

Print capabilities

One- or two-sided printing

Over-the-edge, full-card printing

Full-color images

Capacity

Three-compartment multi-card input hopper: two 50-card hoppers, one 70-card hopper, based on 0.030 in. (0.76 mm) cards

Output hopper: 5 cards, based on 0.030 in.

(0.76 mm) cards

Exception card slide

Encoding

ISO magnetic stripe

Contact and contactless smart card encoder for ISO 14443 A/B, ISO 7816 and MIFARE $^{\!\circ}$

Single-wire connectivity

Supports production of EMV® level1-compliant cards

Security features

SSL/TSL encryption supports Triple DES and AES-128 Software-activated lock with back-up mechanical locks to secure card stock, supplies and rejected cards Bolt-down provision for securing printer to work area Kensington lock compatible (lock sold separately)

Concealed output hopper

Touch-screen display

Displays printer status

Access to printer settings

Dust filter

Bend remedy

User-friendly operation

Automatic card feed

Quick-change ribbon cassettes

Warranties

24-month standard depot warranty Lifetime printhead warranty

Software Compatibility

Compatible with Datacard® CardWizard® instant issuance software

Specifications

Physical dimensions

L 29 in. x W 15 in. x H 13 in. (73.7 cm x 38.1 cm x 33.0 cm)

Weight

47 lbs. (21.3 kg) — approximate, does not include all built-in options or financial options

Connectivity

Ethernet and USB 2.0

IPv4

Card types accepted

ISO/CR-80 size

3.370 in. x 2.125 in. (85.60 mm x 53.98 mm)

PVC, ABS, PET, PET-G, Polycarbonate

Card thickness accepted

0.68 mm to 0.84 mm (25 mil to 33 mil)

Operating environment

60° F to 86° F (15° C to 30° C)

35% to 70%, relative humidity

Storage environment

5° F to 131° F (-15° C to 55° C)

20% to 80%, non-condensing humidity

Electrical requirements (dual voltage, autosensing)

100/120 V, 50/60 Hz 220/240 V, 50/60 Hz

Supplie

Datacard® Certified Supplies featuring Intelligent Supplies Technology™

Automatic ribbon identification and validation Automatic printer settings and offsets

Low ribbon warning

Supplies

YMCKi inhibitor ribbon (750 images) InTM retransfer film (1,000 images) Printer cleaning supplies

Your complete financial instant issuance solution

Manage your card programs the way you want — with exceptional security, reliability and flexibility. The Datacard® CR500™ instant issuance system works seamlessly with Datacard® software, certified supplies and global services to give you a complete financial instant issuance solution.

Software

Datacard® CardWizard® software is the world's best-selling solution for instant issuance of credit, debit and ATM cards. Instantly issue a wide variety of financial cards ondemand and drive new revenue for your financial card program.

Supplies

Datacard® Certified Supplies help you produce highly secure cards instantly. Count on superb image quality and optimize the performance of your Datacard® issuance system.

Services

Datacard Global Services and our worldwide network of authorized service providers are available to answer any questions or promptly address service issues. Backed by more than 40 years of experience, our skilled professionals provide a full range of technical support for your card program.



Memphis, TN 5045 Covington Way Memphis, TN 38134 **1-800-755-0651**

St. Louis, MO 17825 Edison Avenue Chesterfield, MO 63005 **1-888-345-8511**



Corporate Headquarters

11111 Bren Road West
Minnetonka, Minnesota 55343-9015
Phone: +1 952 933 1223
www.datacard.com