



SUPER LIFE® 8000M
SYNTHETIC BLEND MOTOR OILS
For EXTREME POWER

SUPER LIFE® 8000M Products are formulated with a mixture of high-tech synthetic and premium quality base stocks and the advanced additive technology to protect the engines during high temperature conditions.

APPLICATIONS:

SUPER LIFE® 8000M Products are recommended for both gasoline and diesel engines in passenger cars, light- trucks, vans, including turbocharged engines.

SUPER LIFE® 8000M Products meet:

API SM/SL/CF: 5W-20, 5W-30, 5W-40,10W-30,10W-40,20W-50

IL SAC GF-4 & GF-3: 5W-20, 5W-30, 10W-30

Energy Conserving: 5W-20, 5W-30, 10W-30

Ford WSS-M2C153-F/ WSS-M2C929-A/ ESE-M2C153-G/ WSS-M2C946-A: 5W-30

Ford WSS-M2C930-A/WSS-M2C945-A: 5W-20

General Motors GM 6094M: 5W-30

Daimler Chrysler MS6395: 5W-20, 5W-30, 10W-30

Department of Defense Commercial Item Description (CID) – SAE J2362(formerly CID A-A-52039): 5W-30

BENEFITS:

- Maintain protective and thermal breakdown resistant oil films for engine parts.
- Protect against start up wear, rust, corrosion, and harmful deposits (sludge, varnish).
- Flow easily at low temperatures for easy cold starting and rapid warm up.
- Low-friction formula improve gas mileage, and oil economy.
- Preserve engine cleanliness and extend engine life.

TYPICAL CHARACTERISTICS

Test	Method	5W-20	5W-30	5W-40	10W-30	10W-40	20W-50
SAE Viscosity grade	SAE J300						
API Gravity	ASTM D287	33.23	33.03	30.58	30.77	30.21	28.02
Specific gravity @ 15.6 °C (60°F)	ASTMD1298	0.859	0.860	0.873	0.872	0.875	0.887
Viscosity @ 40°C, cSt	ASTMD445	46	62.4	91.8	70.35	98.10	170.0
@ 100°C, cSt		8.39	10.4	14.10	10.50	14.30	19.5

Viscosity Index	ASTMD2270	161	157	158	135	150	131
Flash Point, °C (°F)	ASTMD92	225(437)	225(437)	225(437)	225(437)	230(446)	235(455)
Pour Point, °C (°F)	ASTMD97	-38(-36)	-38(-36)	-38(-36)	-38(-36)	-37(-35)	-26(-15)

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS No: 12023 database on our website at www.amtecol.com OR scan the code for a direct link

