



SUPER LIFE® 7000M

Supreme High Mileage Motor Oils

For Engines with over 75,000 miles

SUPER LIFE® 7000M - Supreme High Mileage Motor Oils are manufactured with special base oils, a special seal-conditioning agent and anti-wear additives to minimize oil leaks in higher mileage engines with over 75,000 miles

Higher mileage engines may perform differently than new ones. This is caused by engine seal deteriorations, brittle gaskets, rings wear and valves that do not seal tightly. These problems cause oil leakage, increase oil consumption, reduced engine performance and premature oil breakdown.

Super Life® 7000M has been developed to help address those problems.

APPLICATIONS:

SUPER LIFE® 7000M - Supreme High Mileage Motor Oils are recommended for all engines used in passenger cars and light trucks. They are safe for both new and rebuilt engines.

API SM

BENEFITS:

- Help to control oil consumption by managing evaporative losses at high temperature.
- Maximize power output.
- Improve engine performance – reduced deposit formation to minimize compression loss and maximize engine performance.
- Condition seals and prevent leaks.
- Easier cold start.

TYPICAL CHARACTERISTICS

Test	Method	Typical results					
		5W-20	5W-30	10W-30	10W-40	20W-50	25W-50
SAE Viscosity Grade	SAE J300						
API Gravity	ASTM D287	33.03	31.52	31.14	30.21	28.75	27.49
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.860	0.868	0.87	0.875	0.883	0.890
Viscosity @ 40°C, cSt	ASTM D445	51.90	74.25	80.5	104.3	171.5	211.17
@ 100°C, cSt		8.5	12	11.8	14.5	20	20.7
Viscosity Index	ASTM D2270	140	158	140	143	135	115
Flash Point, °C (°F)	ASTM D92	210 (410)	210 (410)	210 (410)	220 (428)	225 (437)	225 (437)
Pour Point, °C (°F)	ASTM D97	-36 (-33)	-36 (-33)	-36 (-33)	-36 (-33)	-30(-22)	-30 (-22)

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12021 database on our website at www.amtecol.com OR scan the code for a direct link

