



SUPER LIFE® 7000N

Beneficent High Mileage Motor Oils For Engines with over 75,000 miles

SUPER LIFE® 7000N – Beneficent High Mileage Motor Oils are formulated from high quality base oils with a special seal-conditioning agent and advanced additives to minimize oil leaks in higher mileage engines with over 75,000 miles. These oils protect against sludge and engine rust and corrosion under high and low-temperature operating conditions.

Higher mileage engines may perform differently than new ones. This is caused by engine seal deteriorations, brittle gaskets, rings wear and valves that do not seal tightly. These problems cause oil leakage, increase oil consumption, reduced engine performance and premature oil breakdown. Super Life® 7000N has been developed to help address those problems.



APPLICATIONS:

SUPER LIFE® 7000N – Beneficent High Mileage Motor Oils are recommended for all engines used in passenger cars and light trucks. They are safe for both new and rebuilt engines.

API SN

BENEFITS:

- Help to control oil consumption by managing evaporative losses at high temperature.
- Maximize power output.
- Outstanding wear protection under a wide variety of operating conditions.
- Improve engine performance – reduced deposit formation to minimize compression loss and maximize engine performance.
- Condition seals and prevent leaks.
- Easier cold start.

TYPICAL CHARACTERISTICS

Test	Method	Typical results					
		5W-20	5W-30	10W-30	10W-40	20W-50	25W-50
SAE Viscosity Grade	SAE J300						
API Gravit	ASTM D287	33.42	33.03	31.14	30.77	29.29	27.13
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.858	0.86	0.87	0.872	0.88	0.892
Viscosity @ 40°C, cSt	ASTM D445	52.72	67.36	68.7	103	170	205
@ 100°C, cSt		8.71	10.87	10.4	14.7	19.5	20.5
Viscosity Index	ASTM D2270	143	152	138	148	132	117

Flash Point, °C (°F)	ASTM D92	210 (410)	210 (410)	210 (410)	220 (428)	225 (437)	225 (437)
Pour Point, °C (°F)		-36 (-33)	-36 (-33)	-36 (-33)	-36 (-33)	-30 (-22)	-30 (-22)

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12021 database on our website at www.amtecol.com
OR scan the code for a direct link

