

Garco Sup Speed Sealer

Garco Super Speed Sealer is an excellent sealer for all hardwood flooring applications. It will penetrates the surface, dry fast, will seal in any odors or stains and prepares the surface for topcoating. It can be topcoated with either oil based or water based polyurethanes.

Recommended Uses:

Commercial Floors, All Types Of Residential Floors, Gymnasiums, High Traffic Areas or Areas With High Abrasion and Wear.

Features:

Will seal all hardwoods without raising the wood grain. Provides a smooth finish that can be topcoated with any type of oil based or water based polyurethane. Superb leveling and flow out characteristics. Light amber color enhances natural color of wood.

Surface Preparation:

For best results, use at temperatures between 60° F and 80° F. Allow longer dry times on damp, humid days. Surface must be dry, clean & free from any old finish, wax, grease or dust. Use NOFMA or NWFA recommended sanding schedule for hardwood floors. Clean surface thoroughly to remove dust.

Applying Sealer: Apply a generous amount of sealer onto the applicator and then apply to the surface in an even, consistent coat using full, level strokes. The best application tool for applying sealer is a lambswool applicator. Apply evenly and consistently to the floor in the direction of the grain at a rate of approximately 500-600 square feet per gallon. Do not over-work sealer. Coat only a few board widths at a time, being sure to keep a wet edge.

Abrading Sealer: Use a maroon buffing pad with 180 or 220 sanding strips, changing sanding strips every 75-100 sq ft.

Clean Up: Clean wet spills, tools, etc. with Mineral Spirits.

Solids Content	48 %	Dry Time - To Touch	45 - 60 Minutes
Volatile Content	52 %	Dry Time - To Screen	4 - 6 Hours
Resistance To Skinning	No Skinning	Dry Time - No Tack	24 Hours
Color	No. 7 Gardner	Abrasion Resistance - Sand Test	> 130
VOC (Available)	450, 350, 275	Heel Test	Excellent
Gloss @ 60 Degrees	34	James Machine	< 1%
Coefficient	0.8	Package Stability	No Sediment, No Darkening
Flexibility	Passes 1/8" Mandrel Bend	Weight	7.7 Lb.

Safety Information: DANGER ! FLAMMABLE ! Contains alcohol less than 4% methyl alcohol. Do not use near heat, sparks or open flame. Do not take internally. Harmful or fatal if swallowed. If swallowed, do not induce vomiting. Call physician immediately. Avoid prolonged breathing of vapors. Avoid contact with eyes, prolonged or repeated contact with skin. In case of eye contact, immediately flush thoroughly with water and get medical attention. **Use only with adequate ventilation.**

KEEP OUT OF REACH OF CHILDREN.