



Coatings Excellence Since 1899

Sampson Coatings 1900 Ellen Rd Richmond, VA 23230
toll free: 800.368.2677 local: 804.359.5070 (all non-emergency) fax: 804.353.3706

PRODUCT DATA SHEET

4/4/2014 - This document supercedes all previous product data sheets.

WeatherBrite Acrylic Latex DTM Primer Red

Product Code: 026400

DESCRIPTION

WeatherBrite Acrylic Latex DTM Primer is a premium quality 100% acrylic waterborne primer for use on new, unpainted or previously painted surfaces. It is highly recommended for galvanized metal and may be used under latex, alkyd, oil or strong solvent-based industrial topcoats.

NOTE: Not recommended for use over freshly shot blasted steel.

FEATURES

- Excellent Adhesion
- Corrosion Resistance
- Excellent Color Retention
- One Coat Coverage

SURFACE PREPARATION

Surface should be dry and free of loose paint, rust, scale, dust, mildew, heavy chalking, oil, grease, etc.. Remove loose rust and unsound paint by power washing. Remove mildew, dirt and chalk by washing mildewed surfaces with a solution of 50% bleach and 50% clean water. Apply the solution to mildewed areas using a low-pressure garden sprayer. Thoroughly soak the areas to be treated and allow for it to stand for at least 2-3 hours. Power wash (rinse) the surface, allow it to dry and proceed with painting when all treated areas are completely dry. Wear adequate clothing to protect skin, goggles to protect eyes and wear rubber gloves when spraying the bleach solution. A more professional method is to lightly sandblast the surface followed by broom cleaning to remove debris, then followed by above wash solution and allowing surface to dry completely.

NOTE: Before using WeatherBrite primer over existing old paint, test a small area. Adherence can vary with age and type of existing coating.

APPLICATION

Paint is ready to apply from the can. Do Not Thin. Just stir thoroughly.

Temperature of paint and substrate must be above 45°F for application.

Two coats of topcoat paint may be required to bring out full gloss development.

Do not paint hot metal or in direct sunlight. As this paint dries very quickly.

PHYSICAL PROPERTIES

Vehicle Type:	Styrenated Acrylic
Flash Point:	None
Weight Solids:	47 - 51 %
Volume Solids:	35 - 39 %
Weight Per Gallon:	10.2 - 10.6 lbs/gal
Stormer Viscosity (25°C):	83 - 87 K.U.
60° Gloss:	< 75
English VOC:	< 1.5 lbs/gal
Metric VOC:	< 180 g/l
pH:	8.25 - 9.25
Dry to Touch:	30 min
Dry to Sand/Recoat:	3 - 4 hours
Coverage:	587 sq ft (1 mil dry film)
Application Method:	Spray, brush, roll
Clean Up Solvent:	Warm Soapy Water

CLEAN UP

Clean up application equipment quickly with clean water. This product dries very quickly. Wrap brushes in Saran™ wrap during application delays.

AVAILABLE COLORS

026400 ---- RED

026800 ---- GRAY

SAFETY:

Before starting any of the following procedures, be sure you have and use Personal and Environmental Protective Equipment for all hazards involved. Please read the Material Safety Data Sheet information before using this product.

ADVISORY:

The National Paint and Coatings Association (NPCA) has determined that 80% of all paint and coatings failures can be directly related to improper or inadequate surface preparation.

National Paint and Coatings Association, www.paint.org

ALERT

**HARMFUL OR FATAL IF SWALLOWED;
PROTECT FROM FREEZING!**

PRECAUTIONS:

Dry times are based on laboratory tests at 77 °F and 50% relative humidity. Low temperature, high humidity, heavy application and excessive film build will extend drying times.

WARNING:

Use only with adequate ventilation. Do not breathe vapors or spray mists. Ensure fresh air entry during application and drying. If sanding, applying by spray application, or you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor mist levels above applicable limits, wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Follow manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

If you scrape, sand or remove old paint from any surface, you may release lead dust or other chemical dust hazards. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear a NIOSH-approved respirator to control dust exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

National Institute for Occupational Safety and Health, www.cdc.gov/niosh/programs/
Mine Safety and Health Administration, www.msha.gov

FIRST AID:

If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

SPILL:

If spilled, contain spilled material and remove with inert absorbent.

DISPOSAL:

Dispose of contaminated absorbent, container, and unused contents in accordance with local, state and federal regulations.

STORAGE:

Keep from freezing.

Always consult your Sampson Coatings Representative for Special Problem Applications. The furnishing of the information contained herein does not constitute representation by Sampson that any product is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Sampson or any third party. Sampson assumes no liability for any infringement which may arise out of the use of this product.

Sampson warrants that its products meet the specifications which it sets for them. Sampson DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, including but not limited to warranties of MERCHANTABILITY and FITNESS for a particular purpose. Receipt of products from Sampson constitutes acceptance of the terms of this warranty, contrary provisions of purchase orders notwithstanding. In the event that Sampson finds that the product(s) delivered are out of specification, Sampson will, at its sole discretion, either replace the product(s) or refund the purchase price thereof, and Sampson choice of one of these remedies shall be the buyer's (purchasers) sole remedy. Sampson will under no circumstances be liable for any consequential damages, except in so far as liability mandated by law. Sampson will deliver products at agreed times in so far as it is reasonably able to do so, but Sampson shall not be liable for failure to deliver on time when the failure is beyond its reasonable control.