


# ZIP-LOK

## ZIP-LOK 1 1/2" Standing Seam Panel



### Panel Side Joint

Mechanically Seamed for weathertightness and resistance to wind uplift.

### Applications

Structural roofing on slopes 1" per foot or greater. Continuous lengths without panel laps. Vertical walls, radius barrels and conical tapers (conical panels not available with ribs or clip offsets).

### Substrates

Open purlin / Re-Roof Framing / Plywood / Metal Deck

### Materials

Aluminum (3000 alloy).....	.032"	.040"
Galvanized coated steel (G-90).....	24 ga.	22 ga.
Alum-Zinc coated steel (AZ-50 & AZ-55).....	24 ga.	22 ga.
Copper & lead coated Copper.....	16 oz.	20 oz.
Zinc & Pre-Weathered Zinc .....	.7mm	.9mm

### Standard Gauges

### Finishes

Kynar & Metallic Fluoropolymer Coatings  
Mill Finish, Brushed, Anodized  
Texture: Smooth or Stucco Embossed


### Manufacturing

Factory or Site Roll Formed


### Testing / Agency Approvals

UL-580 Tested UL Listed Class 90 Construction #619  
ASTM E-283 Tested ASTM E-331 Tested

## Components



Some panels configurations are not suitable for all applications. Contact sales & engineering for more information.



### #1069208 Float Clip

Allows for 2 1/16" total thermal expansion of the panel system.  
Holds Panel 3/8" above substrate.




### #1085437 Fixed Clip with Single Lock Panel Application

Single lock panel system (clip will allow for thermal expansion).  
Holds Panel 1/8" above substrate.



### #1085437 Fixed Clip with Double Lock Panel Application

Double lock panel system (does not allow for expansion). Note: Maximum length varies with material selected. Consult M&E engineering for max. panel length.  
Holds Panel 1/8" above substrate.




### #15ZC Ridge/Hip Z Closure

Made from the same material required for the project.  
Supplied in 10'-0" lengths.



### #15GC Continuous Gable/Endwall Clip

Supplied in 10'-0" lengths.



### #15MS Mechanical Seamer Tool

To mechanically seam a single or double lock panel. Available for Rent or Purchase.




Single Lock



Double Lock

### S-5! HD Clamp

Aluminum block for use with S-5! snow retention system and for other practical purposes.





### S-5! ColorGard Snow Retention System

Refer to PS-12 for more information.



### #15HS Hand Seamer Tool

To seam a single lock 1 1/2" panel where the mechanical seamer tool can not reach



### #4418-BP Punched Bearing Plate

18 ga. 4" x 4" galvanized. For clip support over rigid insulation.

Updated November 2012

