



DURALIFE® SYNGEAR 4 EXTREME PRESSURE SYNTHETIC GEAR OILS

Duralife® SynGear 4 – Extreme Pressure Synthetic Gear Oils are specially formulated with selected synthetic base oils and special extreme pressure additives for protection of manual transmissions, transaxles and most types of gearboxes, bearing in passenger cars, trucks, buses and vans.

APPLICATIONS:

Duralife® SynGear 4 – Extreme Pressure Synthetic Gear Oils meet the requirement of the leading car and truck manufacturers who specify the use of a synthetic oil meeting API GL-4.

- ❖ API GL-4
- ❖ MIL-PRF-2105

BENEFITS:

- Provide excellent oxidation, thermal stability.
- Maintain strong oil film under high loading conditions.
- Maintain fluidity at low temperatures.
- Outstanding extreme pressure (EP).
- Excellent anti-wear, antirust, anticorrosion, antifoam properties.

TYPICAL CHARACTERISTICS

Test	Method	Typical results	
SAE Grade		75W-90	80W-140
API Gravity	ASTM D 287	31.52	31.14
Specific Gravity @ 15.6°C (60°F)	ASTMD 1298	0.868	0.870
Viscosity @ 40°C, cSt	ASTMD 445	112.0	313.0
@ 100°C, cSt		15.20	31.20
Viscosity Index	ASTM D 2270	142	138
Flash Point, °C (°F)	ASTM D92	200(392)	210(410)
Pour Point, °C(°F)	ASTM D97	-42(-44)	-36(-32.80)
Timken OK Load, lb	ASTM D2782	65	65

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers.

Reference SDS Number 12045 database on our website at www.amtecol.com
OR scan the code for a direct link

