



DESCRIPTION:

- Fast drying, water clean up, environmentally friendly, penetrating sealer-primer for porous vertical surfaces.
- Specially formulated with 25% clear acrylic resins that penetrate and bind to low density masonry.
- The dried film is resistant to mildew. It contains agents which inhibit the growth of mildew on the surface of the sealer film, and is also resistant to mild acids, and salts.
- Provides a tough and flexible film with excellent scrub resistance and weatherability. May be tinted with latex paint or stain.
- May be mixed with equal parts of latex paint for use as a primer. Mix with exterior latex paint to increase weatherability of the paint.
- May also be used as a binder sealer by adding one gallon of AquaSeal High Solids to five gallons of block filler.
- Exceptional binder for heavily chalked surfaces to improve the adhesion of paint topcoats.
- Protects and seals vertical surfaces of CMU (Concrete Masonry Units), Tilt-Up, Decorative & Fluted Block, Split Face Block, Low Density Brick, Stucco, Limestone, Coral, Grout, Adobe, Chalky Surfaces, Pottery and many other porous surfaces.
- Elimination of cascading water must be addressed prior to AquaSeal High Solids application.
- Designed for above grade use only and should not be used on applications exposed to hydrostatic water pressure.
- Waterproofing Sealer has surpassed requirements for water repellency set forth in Fed. Spec TT-C-555B, Section 3.3.3.

ORDERING:

- Available in 5 gallon buckets only.
- Coverage is between 100 to 300 square feet per gallon, per coat, depending on the type of surface and porosity.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
236 AQUA SEAL HIGH SOLIDS 5G	023605	5G	760428023653	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.

236 AQUA SEAL HIGH SOLIDS WATERPROOFER SEALER / BONDING PRIMER

PROPERTIES	
Weight per Gallon	8.57 lbs.
Color(s)	Milky (wet) - Clear (dry)
Gloss	Low Sheen
VOC Content	148.2 Grams per Liter (cal.)
Viscosity	34 KU @ 75° F
Solid Content by Weight	22.0%
Solid Content by Volume	22.8%
Resin	Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity. High humidity, high film thickness, or cooler temperatures will lengthen dry times.	To Touch: 1/2 Hour To Recoat: 1 Hour

- Acrylic film forming process may require several weeks at 75° F to develop final adhesion and water resistance.

CLEANUP:

- Roller covers and spray equipment can be cleaned with soapy water.
- Dried sealer will be difficult to remove from any surface.

DIRECTIONS FOR USE AND SURFACE

PREPARATION:

- Remove all dirt, efflorescence, grease, oil, waxes, release agents, peeling paint, excessive chalk and other foreign material that would interfere with the adhesion of the sealer.
- Repair all voids, cracks, surface breaks, excessive mortar shrinkage and crevices.
- If used as a water proofer the surface must be bare.
- Not designed to remedy water intrusion problems associated with poor workmanship or poor material quality.

APPLICATION:

- Do not dilute
- Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50° F within the first 24 hours of application.
- For best results apply with a low-pressure garden sprayer or airless paint sprayer.
- Flood coat the surface liberally beginning at the top and allow AquaSeal to run down the surface about 8 inches.
- For best penetration and sealing, back roll the wet coat to uniformly force the sealer into the surface. A minimum of 2 liberal saturated coats is always recommended.
- Applies milky white to aid in even application, but dries clear.