



### DESCRIPTION:

- Fast drying, penetrating paint conditioner that brings color luster back for vertical mobile home surfaces.
- Provides a tough and flexible film with excellent scrub resistance and weatherability that protects and seals vertical mobile home surfaces and painted metal surfaces.
- Can be used on vinyl siding.

### ORDERING:

- Available in 1 gallon jugs.
- Coverage is 100 to 300 square feet per gallon, per coat, depending on the type of surface and porosity.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
0535 MOBILE HOME RESTORE 1G	053501	1G	760428053513	14.5 x 9 x 12	4	48 Cases

### STORAGE & HANDLING:

- **CONTAINS SOLVENTS, WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.**
- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush immediately with large amounts of water, for at least 15 minutes. If swallowed, get medical attention immediately. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.

### PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.

# 535 MOBILE HOME RESTORE

<b>PROPERTIES</b>	
Weight per Gallon	8.42 lbs.
Color(s)	Milky (wet) - Clear (dry)
Gloss	Low Sheen
VOC Content	26 Grams per Liter (cal.)
Viscosity	28 KU @ 75° F
Solid Content by Weight	11.0%
Solid Content by Volume	10.0%
Resin	Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1/2 Hour To Recoat: 1 Hour

## **DIRECTIONS FOR USE AND SURFACE PREPARATION:**

- Power wash all dirt, mold, mildew and excessive chalk off and allow to completely dry before applying Mobile Home Restore.

## **APPLICATION:**

- Mobile Home Restore may be applied with a brush, roller or may be sponged on.
- Be sure to wear rubber gloves when using a sponge.
- Apply the product at a thin even rate, and avoid allowing it to run down the surface.
- Goes on milky white to aid in the even application but dries to the natural color.
- Can be painted over within 2 hours of application and will act as a primer for water-based paints.

## **CLEANUP:**

- Roller, brushes, sponges and spray equipment may be cleaned up with water.