

345 HOT STUCCO BLOCK FILLER (SMOOTH)



DESCRIPTION:

- An Ethylene Chloride-Vinyl Acetate Latex based block filler especially formulated for use over “HOT” block and stucco.
- Provides a uniform base for application of more costly finish coats which would otherwise be absorbed by an unsealed surface requiring additional re-coats to achieve uniform appearance.
- The unique properties of this product allow it to lock in alkalinity, resist efflorescence, and deterioration caused by moisture.
- Anvil #345 “HOT” Block Filler prevents “burn through” caused by high pH in new stucco or masonry.

ORDERING:

- Available in 1 gallon cans and 5 gallon buckets.
- Coverage is approximately 75 to 150 square feet per gallon, per at recommended dry film thickness of 4 to 8 Mils. This includes material which has been used to fill the pores of rough block, masonry, etc.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
0345 HOT STUCCO FIL/PRMR 1G	34501	1G	760428034512	14" x 14" x 8"	4	54 Cases
0345 HOT STUCCO FIL/PRMR 5G	34505	5G	760428034550	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

345 HOT STUCCO BLOCK FILLER (SMOOTH)

PROPERTIES	
Weight per Gallon	11.4 lbs.
Color(s)	White
Gloss	Flat
VOC Content	74.3 G/L (cal.)
Viscosity	120 KU @ 75° F
Solid Content by Weight	55%
Solid Content by Volume	40%
Resin	Ethylene Chloride Vinyl Acetate
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1/2 to 1 Hour To Recoat: 2 to 3 Hours Dry: 4 to 6 Hours

USES:

- To prime, fill, and seal pores in rough stucco, concrete block, cement and plaster and prevent pH burn through.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Remove all loose dirt, chalk, mildew and other surface contaminants. Pressure clean and apply mildewcide for proper preparation for exterior surfaces. May be tinted to permit the use of economical, lower hiding topcoats.

THINNING:

- None required. Use water if desired. 1/2 Pt. per gallon is permissible.

APPLICATION:

- Use brush, roller or spray. Best results are obtained when using airless spray equipment for more porous applications.

TINTING:

- Light tones only

CLEANUP:

- Water