



ROOF-TEC ACRYLIC WHITE ELASTOMERIC ROOF COATING



6600

AVAILABLE SIZES
1 GALLON CANS
5 GALLON PAILS

RESIN: Acrylic Emulsion

COLOR: Brilliant White

GLOSS: low sheen

SOLIDS BY WEIGHT: 44.9%

SOLIDS BY VOLUME: 30.0%

VISCOSITY: 108 KU@75F

ELONGATIONS PERCENT: 100

WEIGHT PER GALLON: 10.6 lbs

FLASH POINT: none

RECOMMENDED COVERAGE:
60 sq. feet per coat depending on the
type of roof

DRYING TIME@75F&50%RH:

To touch: 1 to 2 hours

To recoat: 24 hours

Drying times are influenced by
ambient temperature and relative
humidity. Do not apply when
temperature is below 50F.

CLEAN-UP: soap & water

VOC: 81.0 grams/liter

USES, FEATURES & BENEFITS

Anvil's ROOF-TEC Acrylic Elastomeric Roof Coating is an acrylic latex roof coating formulated to provide superior bridging of the coating over seams and small separations. ROOF-TEC Acrylic exceeds performance of similar coatings of this type for adhesion and longevity. Its brilliant white finish not only beautifies, it reflects up to 90% of the sun's rays lowering heat buildup and reducing air conditioning costs. Stays brighter longer since it contains a fungicide to resist mildew growth on the product film. Roofs must have adequate pitch to allow water to run off.

DIRECTIONS FOR USE AND SURFACE PREPARATION

All surfaces must be clean and free of dirt, dust, rust, mildew and other surface contaminants. Remove contaminants by sandblasting, high-pressure water blasting or mechanical methods. Rinse with water and let dry completely. Substrate must be dry at time of applying primer and subsequent coating.

Metal Roofs: Remove rust mechanically and prime with Anvil Rust Inhibitive Primer 1606. Replace loose fasteners. Seal seams and old fasteners with Anvil Seam Seal Elastomeric Brush Grade Caulk 1220 and Seam Tape 9414. Allow caulked areas to dry 24 hours. If previously coated, prime with Anvil AquaSeal High Solids 236.

Concrete Roofs: Repair holes or any weakened areas with high quality masonry cement. Repair cracks with Anvil Seam Seal Elastomeric Brush Grade Caulk 1220. Prime all areas with Anvil AquaSeal High Solids 236. Let dry 24 hours.

Built-Up Roofs: Remove all loose gravel and clean thoroughly. Repair cracks and joints with Anvil Seam Seal 1220 and Seam-Tape 9414. Allow caulked areas to dry 24 hours. Apply prime coat of ROOF-TEC 6600, sealing completely all of the gravel. Let dry 24 hours.

Asphalt Roofs: Clean surface thoroughly. Prime with Anvil AquaSeal High Solids 236. Repair cracks and seams with Anvil Seam Seal 1220 and Seam Tape 9414. Let dry 24 hours.

Previously Coated Polyurethane Foam Roofs: Clean surface thoroughly. Prime with Anvil AquaSeal High Solids 236. Repair cracks and joints with Anvil Seam Seal 1220 and Seam Tape 9414. Allow caulk to dry 24 hours.

ROOF-TEC APPLICATION: Apply with roller or airless sprayer. Airless pump set at 1,500 to 2,000 psi delivering 1 to 2 gallon per minute using spray tip of .026-.035. Allow 24 hours between coats. Apply only when temperatures are above 50°F and when humidity is below 95% for the next 24 rain free hours. If the roof is hot or day is windy, apply a mist-spray with water just before application to avoid sealer from drying too fast. Two or three (for warranty) coats at the rate of 60 sq. ft. per gallon are needed for proper sealing. Apply each coat perpendicular to the first coat. Do not thin product. Apply at package consistency.

CLEAN UP

Roller covers and spray equipment should be cleaned with soap and water

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a

wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

CLOSE CONTAINER AFTER EACH USE. USE WITH ADEQUATE VENTILATION. USE PROTECTIVE CLOTHING TO AVOID CONTACT WITH SKIN AND EYES. KEEP AWAY FROM CHILDREN. KEEP FROM FREEZING

10-YEAR LIMITED WARRANTY AVAILABLE

Anvil Paints & Coatings expressly warrants, subject to the Exclusion of Warranties provision set forth below, that its products shall be fit for the ordinary purposes for which such products are intended for a period of ten (10) years. NO OTHER EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES including implied warranties of MERCHANTABILITY and/or fitness for a particular purpose shall be applicable to any product(s) of Anvil Paints & Coatings, except to the extent that any of such products are specifically covered by an expressed warranty that is provided in writing to a particular purchaser who submits the Job Procedure Checklist to Anvil Paints & Coatings and is issued a written warranty by an authorized employee of Anvil Paints & Coatings. In the event of a breach of any product warranty extended by Anvil Paints & Coatings, Anvil's liability and the associated claimant's sole and EXCLUSIVE REMEDY is EXPRESSLY LIMITED to the replacement of the defective product(s) FOB Largo FL on a pro rata basis according to the original sale price, so that the claimant will effectively be charged only for that portion of the normal useful life of the defective product(s) which has elapsed since the purchase date of the product(s). Under no circumstances shall Anvil Paints & Coatings be liable for any consequential damages, including any labor costs that may be associated with a breach of any product warranty extended by Anvil Paints & Coatings. EXCLUSION OF WARRANTIES Anvil Paints & Coatings assumes no warranty regarding the installation of its products. In addition, if Anvil Paints & Coatings products are not properly installed, then no product warranties, expressed or implied shall apply to the products that have been improperly installed.

Request Job Procedure and Warranty from:



04/2016 Supersedes all prior publications GRO



BRILLIANT WHITE

ACRYLIC EMULSION DURABLE

RESISTS MILDEW & ALGAE

BRIDGES HAIR-LINE CRACKS

REDUCES ROOF TEMPERATURE

SOLOR-REFLECTIVE

PROTECTS & BEAUTIFIES

ENERGY SAVING

THICK SEAMLESS PROTECTION

SOAP & WATER CLEAN-UP