



## ***SUPER LIFE® 2500*** **MOTOR OILS**

***SUPER LIFE® 2500 Products*** are formulated from superior quality base stocks with advanced additive packages to maintain a stable protective oil film on vital engine parts. The use of these motor oils lead to increase engine power and improved fuel economy .They can be used in both normal driving conditions including stop-and-go service ,heavy load and in all conditions of weather and road .

### **APPLICATIONS:**

***SUPER LIFE® 2500 Products*** are recommended for gasoline and diesel engines of all kinds of trucks, passenger cars and vans .These motor oils meet all the requirements of high capacity gasoline and diesel engines operating in severe conditions such as heavy load, extreme hot and cold weather and frequent stop-and-go service

API SF/SE/CC

### **BENEFITS:**

- Improve engine performance and fuel efficiency. Help engine to start up quickly and run smoothly.
- Effective detergent and dispersant that prevent sludge deposits and keep internal engine parts clean .
- Anti-wear properties and anti-foaming properties provide superior engine protection .
- Superior thermal stability and anti-oxidant at high temperature

### **TYPICAL CHARACTERISTICS**

Test	Method	Typical results				
		40	50	10W-40	15W-40	20W-50
SAE Viscosity grade	SAE J300	40	50	10W-40	15W-40	20W-50
API Gravity	ASTM D287	28.38	27.49	29.29	28.38	27.49
Specific gravity @ 15.6 °C (60°F)	ASTMD1298	0.885	0.890	0.880	0.885	0.890
Viscosity @ 40°C cSt	ASTMD445	156.9	244.6	120.40	133.8	196.0
@ 100°C cSt		15.5	21.0	14.0	15.1	20.8
Viscosity Index	ASTMD2270	100	100	115	115	120
Flash Point, °C (°F)	ASTMD92	210 (410)	220 (428)	220 (428)	220 (428)	220 (428)
Pour Point, °C (°F)	ASTMD97	-12 (10.4)	-12 (10.4)	-25 (-13)	-25 (-13)	-25 (-13)

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

*Reference SDS Number 12021 database on our website at [www.amtecol.com](http://www.amtecol.com)  
OR scan the code for a direct link*

