



## ***SUPER LIFE® 7500M*** **SUPREME MOTOR OILS**

*SUPER LIFE® 7500M Products* are manufactured with the premium quality base oils , a shear stable viscosity index improver and a latest additive system to provide extraordinary engine protection under all severe driving conditions, including heavy load and stop-and-go conditions , rapid acceleration , sudden stops and high revving all push the engine to work harder and run hotter. They are specifically designed to meet the demands of today’s high- performance modern engines.

### **APPLICATIONS:**

*SUPER LIFE® 7500M Products* are recommended for gasoline engine used in passenger cars, light-duty trucks, vans, including turbocharged engines.

*SUPER LIFE® 7500M Products* meet:

API SM/SL: SAE 30, 40, 50, 5W-20, 5W-30, 10W-30, 10W-40, 20W-50

IL SAC GF-4 & GF-3: 5W-20, 5W-30, 10W-30

Energy Conserving: 5W-20, 5W-30, 10W-30

### **BENEFITS:**

- Ensure effective protective oil films for engine parts and excellent resistance to thermal breakdown at high temperature
- Flow easily at low temperature for easy cold starting and rapid warm up
- Help protect against start up wear, rust and corrosion
- Protect against harmful deposits (sludge, varnish)
- Low-friction formula help improve gas mileage, fuel economy, oil economy
- Extend engine life
- Excellent at maintaining engine cleanliness

### **TYPICAL CHARACTERISTICS**

| Test                               | Method    | Typical Results |               |               |              |                |               |               |              |
|------------------------------------|-----------|-----------------|---------------|---------------|--------------|----------------|---------------|---------------|--------------|
|                                    |           | 30              | 40            | 50            | 5W-20        | 5W-30          | 10W-30        | 10W-40        | 20W-50       |
| SAE Viscosity grade                | SAE J300  |                 |               |               |              |                |               |               |              |
| API Gravity                        | ASTM D287 | 27.30           | 26.60         | 26.25         | 33.03        | 30.02          | 30.21         | 29.47         | 28.38        |
| Specific gravity @ 15.6°C (60°F)   | ASTMD1298 | 0.891           | 0.895         | 0.897         | 0.860        | 0.865          | 0.875         | 0.879         | 0.885        |
| Viscosity @ 40°C, cst @ 100°C, cst | ASTMD445  | 87.9<br>11      | 136.8<br>14.5 | 219.3<br>20.0 | 47.5<br>8.25 | 66.75<br>11.10 | 72.88<br>11.0 | 98.95<br>14.0 | 160<br>17.85 |
| Viscosity index                    | ASTMD2270 | 111             | 105           | 105           | 149          | 159            | 141           | 144           | 123          |
| Flash point, °C (°F)               | ASTMD92   | 220<br>(428)    | 230<br>(446)  | 235<br>(455)  | 205<br>(401) | 205<br>(401)   | 210<br>(410)  | 220<br>(428)  | 225<br>(437) |

|                        |         |               |               |               |              |              |              |              |              |
|------------------------|---------|---------------|---------------|---------------|--------------|--------------|--------------|--------------|--------------|
| Pour point, °C<br>(°F) | ASTMD97 | -12<br>(10.4) | -12<br>(10.4) | -12<br>(10.4) | -35<br>(-31) | -36<br>(-33) | -32<br>(-26) | -32<br>(-26) | -26<br>(-15) |
|------------------------|---------|---------------|---------------|---------------|--------------|--------------|--------------|--------------|--------------|

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

*Reference SDS Number 12021 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link*

