

## SUPER LIFE® 7000

# **High Mileage Motor Oils For Engines with over 75,000 miles**

SUPER LIFE® 7000 High Mileage Motor Oils are manufactured with special base oils, a special seal-conditioning agent and anti-wear additives to meet the needs of higher mileage engines with over 75,000 miles

Higher mileage engines may perform differently than new ones. This is cause by engine seals deteriorations, brittle gaskets, rings wear and valves that do not seal tightly. These problems cause oil leakage, increase oil consumption, reduced engine performance and premature oil breakdown.

Super Life® 7000 has been developed to help address those problems.



#### **APPLICATIONS:**

SUPER LIFE® 7000 Higher Mileage Engine Motor Oils are recommended for all engines used in passenger cars and light trucks. They are safe for both new and rebuilt engines.

API SL

#### **BENEFITS:**

- Reduce oil consumption.
- Improve engine performance reduced deposit formation to minimize compression loss and maximize engine performance.
- Condition seals and prevent leaks.
- Easier cold start.

### TYPICAL CHARACTERISTICS

Test	Method	Typical results						
SAE Viscosity Grade	SAE J300	5W-20	5W-30	10W-30	10W-40	20W-50	25W-50	
API Gravity	ASTM D287	31.52	31.14	29.66	29.29	27.49	26.60	
Specific Gravity @ 15.6 °C (60°F)	ASTM D1298	0.868	0.870	0.878	0.880	0.890	0.895	
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	52.60 8.55	73.60 11.0	69.2 10.5	101.5 14.0	185.8 19.5	202 20.0	
Viscosity Index	ASTM D2270	139	140	139	140	120	115	

Flash Point, °C (°F)	ASTM D92	210	210	210	220	225	225
		(410)	(410)	(410)	(428)	(437)	(437)
Pour Point, °C (°F)	ASTM D97	-30	-30	-30	-30	-26	-25
		(-22)	(-22)	(-22)	(-22)	(-15)	(-13)

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

#### **WARNING:**

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers



Reference SDS Number 12021 database on our website at <a href="www.amtecol.com">www.amtecol.com</a> OR scan the code for a direct link