



***SUPER LIFE® 8000M Euro***  
***SYNTHETIC BLEND MOTOR OILS***  
***For EXTREME POWER***

*SUPER LIFE® 8000M Euro Products* are formulated with a mixture of high-tech synthetic and premium quality base stocks and the advanced additive technology to protect the engines during high temperature conditions.

**APPLICATIONS:**

*SUPER LIFE® 8000M Euro Products* are recommended for both gasoline and diesel engines in passenger cars, light- trucks, vans ,including turbocharged engines.

*SUPER LIFE® 8000M Euro Products* meet :

API SM/SL/CF : 5W-20, 5W-30,5W-40, 10W-30,10W-40,10W-50, 15W-40, 20W-50

IL SAC GF-4 & GF-3: 5W-20, 5W-30, 10W-30

Energy Conserving: 5W-20, 5W-30, 10W-30

ACEA A1/B1 : 5W-20,5W-30,5W-40, 10W-30,10W-40, 15W-40

ACEA A3/B3/B4 : 5W-30,5W-40, 10W-40 ,10W-50, 15W-40, 20W-50

ACEA A5/B5 : 5W-30 , 10W-30

ACEA C1 /C2 : 5W-30

ACEA C3,MB 229.3/229.5/229.31/229.51,MS6395K, BMW LL-04: 5W-30,5W-40

VW505.01/502.00/505.00/507.00/506.01,GM4718M/6094M:5W-30,5W-40,10W-30

FORD M2C929A/M2C930A/ M2C945A /M2C946A: 5W-20,5W-30, 10W-30

DAIMLER CHRYSLER MS6395N,VW503.00 ,FORD WSS-M2C205A/925A :  
5W-20,5W-30,10W-30

DAIMLER CHRYSLER MS6395G,VW 501.01/503.01/506.00/506.01/502.00/505.00,

MB 229.3/229.5 , BMW LL-01 , FORD M2C912A/M2C153 G, H : 10W-40,15W-40

MIL-L-2104B / MIL-L- 46152 : 5W-30, 5W-40, 10W-30

RENAULT RN 0700/0710: 5W-30

**BENEFITS:**

- Maintain protective and thermal breakdown resistant oil films for engine parts.
- Protect against start up wear, rust, corrosion, and harmful deposits (sludge, varnish).
- Flow easily at low temperatures for easy cold starting and rapid warm up.
- Low-friction formula improve gas mileage, and oil economy.
- Preserve engine cleanliness and extend engine life.

**TYPICAL CHARACTERISTICS**

Test	Method	Typical Results							
		5W-20	5W-30	5W-40	10W-30	10W-40	10W-50	15W-40	20W-50
SAE Viscosity grade	SAE J300								
API Gravity	ASTM D287	33.23	33.03	30.58	30.77	30.21	30.02	29.66	28.02
Specific gravity @ 15.6 °C (60°F)	ASTMD1298	0.859	0.860	0.873	0.872	0.875	0.876	0.878	0.887
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTMD445	46	62.4	91.8	70.35	98.10	124.5	106.0	170.0
		8.39	10.4	14.10	10.50	14.30	17.9	15.2	19.5
Viscosity Index	ASTMD2270	161	157	158	135	150	160	151	131
Flash Point, °C (°F)	ASTMD92	225 (437)	225 (437)	225 (437)	225 (437)	230 (446)	232 (449.6)	232 (449.6)	235 (455)
Pour Point, °C (°F)	ASTMD97	-38 (-36)	-38 (-36)	-38 (-36)	-38 (-36)	-37 (-35)	-37 (-35)	-37 (-35)	-26 (-15)
HTHS Viscosity @ 150°C ,cP	ASTM D4683	2.62	3.55	3.60	3.45	3.82	4.10	4.25	4.33
Noack , %wt	ASTMD5800	13.5	12.85	12.65	12.68	12.5	6.6	6.8	6.2

*The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS No: I2023 database on our website at [www.amtecol.com](http://www.amtecol.com)  
OR scan the code for a direct link

