



DURALIFE® PRE-DILUTED 50/50 ANTIFREEZE / COOLANT

Duralife® Pre-diluted 50/50 Antifreeze / Coolant is an ethylene glycol/water based formulation. It is ready to use without adding water. This product protects all metal surfaces within the cooling system including solder, copper, brass, steel, cast iron, and aluminum. The effectiveness of the coolant is improved by the anti-foam properties which works by preventing air bubbles from forming and interfering with the coolants ability to cool.

APPLICATIONS:

Duralife® Pre-diluted 50/50 Antifreeze / Coolant is recommended for automotive and truck cooling systems and other industrial machines.

Duralife® Pre-diluted 50/50 Antifreeze / Coolant provides protection over a temperature range from -37°C (-34°F) to 129°C (265°F).

It meets the following performance requirements:

- ❖ ASTM D3306, D 4985, D4340
- ❖ SAE J1034, J1941
- ❖ Chrysler MS7170, Ford ESE -WSSM97B44A, GM 1825M/1899M, GSA A-A-870, TMC RP-329/302B, CID A-A-52624, John Deere H24A1 & H24C1, Freightliner 48-22880, Mack Truck, Volvo-GM Heavy Duty Truck, Chrysler MS7170 Section A&B -14.

BENEFITS:

- This product will provide up to 4,000 hours or 150,000 miles in-field service life.
- Constant cooling through improved heat exchange in the cooling system.
- Prevents foaming and provides protection against rust and corrosion.
- No effects on automotive rubber hoses, gaskets and synthetic parts.
- Low silicate formulation that reduces drop-out and silicate gel formation.
- Improved hard water stability, due to the absence of phosphates.
- Compatibility with most major brands of coolant.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
PH	ASTM D1287	7.0 – 11.0
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	1.02 – 1.15
Freezing point, °C(°F) max	ASTM D1177	-37 (-34)
Boiling point , °C (°F) min	ASTM D1120	108 (226)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING: Corrosion liquid! Harmful if takes internally. Keep out of reach of children and avoid contact with eyes. Do not discharge used liquid into drains.

Reference SDS Number 12028 database on our website at www.amtecol.com
OR scan the code for a direct link.

