

**Buy Winston service parts
online!**

Factory direct at
www.winstonindustries.com.



WINSTON INDUSTRIES
THE TASTE OF INNOVATION



INSTRUCTIONS

QUARTERLY PREVENTATIVE MAINTENANCE SHORTENING FILTERS KFC DOMESTIC & INTL MODELS - F662, F552

TOOLS NEEDED:

A Phillips head screwdriver is needed for inspection purposes. Other tools may be required for servicing a discovered problem.

INSTRUCTIONS:

PERFORM ALL OF THE FOLLOWING PROCEDURES QUARTERLY: **IMPORTANT:** These instructions are for a quarterly inspection only. Daily cleaning procedures must be followed as described in the Use and Care Manual.

1. Perform daily cleaning procedures as outlined in the Filter Use and Care Manual.
2. Inspect all hoses for leaks or other signs of wear.
3. Inspect wheels for signs of wear and make sure all nuts and bolts are secure.
4. Inspect O-rings on hose nozzles. There should be one o-ring on each nozzle.

DANGER: shortening filter should be disconnected from power supply when performing the following steps:

1. Inspect power cord for loose or frayed connections.
2. Open top panel – inspect wiring for loose connections, burnt wires, etc.
3. Inspect inside of motor housing for signs of leaking shortening. Particularly check around the pump/motor connection and the pump lines.
4. Make sure all pump line (tubing) connections are tight and secure.