



## ***SUPER LIFE® ATV/UTV 4T FS*** **PREMIUM FULL SYNTHETIC 4-STROKE ATV/UTV MOTOR OILS**

***SUPER LIFE® ATV/UTV 4T FS Products*** are premium quality synthetic lubricants specially designed to ensure good protection for the engine, wet clutch and gearbox used by ATVs (All-Terrain Vehicles), UTVs (Utility Vehicles) and other power sports application. They ensure highest degree of reliability of maximum performance of the engine even under severe operating conditions. They are formulated with Synthetic base stocks and a unique additive package chosen for exceptional wear protection, sludge and varnish resistance, and thermal stability.

### **APPLICATIONS:**

***SUPER LIFE® ATV/UTV 4T FS Products*** are recommended for all types of 4-stroke ATVs /UTVs of manufacturers including POLARIS, HONDA, SUZUKI, YAMAHA, KAWASAKI, CAN-AM, KUBOTA, JOHN DEERE, ARCTIC CAT, BOMBARDIER, etc.

API SN  
 JASO MA/MA 2 ISO-L-EMA2

### **BENEFITS:**

- Help engine reach maximum performance and power, quick starting up .
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability. Non-friction modified to maintain clutch effectiveness.
- Protect well heavy loaded parts in very severe conditions of operating : high speed, high temperature, rough roads .
- Anti-wear properties, lower corrosion and friction. Provide excellent protection for transmissions and wet clutches.
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly .
- Excellent fuel saving, lengthen the oil changing intervals, economize everything . Prolong engine life .
- Provide good characteristics in harmful deposit control to help keep the engine and gearbox running cleaner and provides good gearbox protection for incorporated gearboxes .

### **TYPICAL CHARACTERISTICS**

Test	Method	Typical Results			
		0W-40	10W-40	5W-50	10W-50
SAE Viscosity grade	SAE J300	0W-40	10W-40	5W-50	10W-50
API Gravity	ASTM D287	34.19	34.38	34.00	33.03
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.854	0.853	0.857	0.860
Viscosity @ 40°C cSt @ 100°C cSt	ASTM D445	86.0	98.0	130.0	136.0
		14.80	15.01	20.35	19.30

Viscosity Index	ASTM D2270	180	160	180	162
Flash Point, °C (°F)	ASTM D92	228(442)	228(442)	230(446)	230(446)
Pour Point, °C (°F)	ASTM D97	-50(-58)	-39(-38)	-45(-49)	-38(-36)
Low temperature (°C) Cranking Viscosity, cP	ASTM D5293	5800 @-35 °C	5600 @-25 °C	5750 @-30 °C	6200 @-25 °C
Noack, wt%	ASTM D5800	7.50	7.04	5.90	6.91
Total Base Number, mgKOH/g	ASTM D2896	8.5	8.5	8.5	8.5

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference MSDS Number 12022 database on our website at [www.amtecol.com](http://www.amtecol.com)*