



CONCRETE & MASONRY CLEANER & ETCHER



RESIN: Phosphoric acid and detergents/degreasers

COLOR: Brown

WEIGHT PER GALLON:
10.41 lbs.

FLASH POINT: None

COVERAGE:
Garage Floors one gallon Cleaner & Etcher to two gallons water for 1,800 Sq ft of concrete.

CLEANUP: Soapy water

VOC: 0.0 grams/liter

1450



Available size - 1 Gallon Jug
Makes up to 4 Gallons

DESCRIPTION

Anvil Clean & Etch is an etching solution used to clean and de-grease bare concrete surfaces to improve penetration and adhesion of paint, stains, and sealants. It also neutralizes new concrete and removes light rust stains from concrete, steel, and other masonry surfaces. Use on interior/exterior uncoated surfaces such as garage floors driveways patios, carports, basement floors, and concrete walls. Clean & Etch removes grease, oil, auto fluids, rust and dirt. It is biodegradable and safe to use near grass and plants. Do not use on marble, granite, terrazzo, colored concrete, brass bronze or copper.

Wipe excess oil and grease spills. Scrape and sweep away dirt. Use de-greaser to remove heavy oily stains.

For garage floors and other smooth-troweled concrete, mix 1 part of ANVIL Clean & Etch with 2 parts of water. For broom finish concrete, mix 1 part to 3 parts of water. Use a plastic container for mixing. Always add Clean & Etch to water.

Read all instructions thoroughly. Wear protective clothing, safety goggles, acid resistant rubber gloves, and protective footwear. Avoid splashing. Spraying is not recommended. Use plastic sprinkling can. Working a 10 ft. X 10 ft. section at a time, dampen surface with water. Using a non-metal stiff-bristled brush or broom, scrub solution into surface until foaming action stops. Triple rinse surface with a strong stream of water, scrubbing while rinsing to ensure removal of all material. Surface should feel rough (like 150 grit sandpaper). When dry, check surface by applying a few drops of water. Water should penetrate quickly (if not, re-etch affected area). Heavily stained areas or older stains may require re-etching. Allow surface to dry thoroughly (24 hours) before applying paint or stain.

Do not apply to concrete that has already been sealed,

XXXXXXXXXXXXXXXXXXXX

This product is manufactured to rigid control specifications. It is impossible to control the use and application. Therefore, the manufacturers sole liability is limited to replacing quantities of product proven to be defective. The manufacturer disclaims any liability for the cost of labor to repaint or any other use of the product.



FEATURES & BENEFITS

BIODEGRADABLE

HELPS REMOVE GREASE AND OIL STAINS

INTERIOR OR EXTERIOR USE

NO FUMES OR ODOR, NO VOCs

PREPARES SURFACE FOR PAINTING

USE ON SMOOTH TROWELED CONCRETE

CLEAN AND ETCH IN 1 STEP

EASY WATER CLEAN-UP

5/2017

0.0 VOC

